

IN CASE OF TRANSPORTATION EMERGENCY CONTACT:

**CHEMTREC:(800) 424-9300**

-----  
ALL OTHER INQUIRIES:  
(770) 904-7042 // [www.ciscochem.com](http://www.ciscochem.com)  
266 Rue Cezzan Lavonia, GA 30553



## 1. IDENTIFICATION

170 SOLVENT

SYNONYMS: Dearomatized Mineral Spirits

## 2. HAZARDS IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: FLAMMABLE LIQUIDS - Category 4  
ACUTE TOXICITY: INHALATION - Category 4  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3  
ASPIRATION HAZARD - Category 1

SIGNAL WORD: DANGER

HAZARD STATEMENTS: COMBUSTIBLE LIQUID.  
HARMFUL IF INHALED  
CAUSES SKIN AND EYE IRRITATION  
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS  
MAY CAUSE DROWSINESS AND DIZZINESS

PRECAUTIONARY STATEMENTS  
PREVENTION: Wear protective gloves. Wear eye or face protection. Keep away from flames and hot surfaces. - No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

RESPONSE: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If Skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

STORAGE: Store locked up. Store in a well ventilated place, keep cool.

DISPOSAL: Dispose of contents and container in accordance with all local, regional, national regulations

### 3. COMPOSITION

SUBSTANCE/MIXTURE: Substance

OTHER MEANS OF CLASSIFICATION: Dearthmatized mineral spirits

CAS # 64742-47-8

INGREDIENT NAMES: %

C9-C15 Cycloalkanes: 60-100  
C9-C15 Alkanes 15-40  
C9-C15 Aromatics 0.1 - 1

Any concentrations shown as a range is to protect confidentiality or is due to process variation.

OCCUPATIONAL EXPOSURE LIMITS, IF AVAILABLE, ARE LISTED IN SECTION 8

### 4. FIRST AID MEASURES

#### DESCRIPTION OF NECESSARY FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if Respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SKIN CONTACT; Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before Reuse. Clean shoes thoroughly before reuse.

INGESTION: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### MOST IMPORTANT SYMPTOMS/EFFECTS.ACUTE POTENTIAL ACUTE HEALTH EFFECTS

EYE CONTACT: Causes eye irritation

INHALATION: Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness

SKIN CONTACT: Causes skin irritation

INGESTION: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

OVER EXPOSURE SIGNS/SYMPTOMS: Adverse symptoms may include the following:

EYE CONTACT: pain or irritation, watering & redness

INHALATION: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness

SKIN CONTACT: Irritation and/or redness

INGESTION: nausea or vomiting

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY

NOTES TO PHYSICIANS: If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

SPECIFIC TREATMENTS: Treat symptomatically and supportively

PROTECTION OF FIRST- AIDERS:

No action shall be taken involving any personal risk or without suitable training. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See Toxicological information (Section 11)

## 5. FIRE FIGHTING MEASURES

### SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

### EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet

### HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:

Decomposition products may include the following materials:  
Carbon dioxide, carbon monoxide

### SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

### SPECIAL PROTECTIVE EQUIPMENT

FOR FIRE FIGHTERS:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

FOR NON EMERGENCY PERSONNEL: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard Area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

FOR EMERGENCY RESPONDERS:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".

ENVIRONMENTAL PRECAUTIONS:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

SMALL SPILL:

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL:

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. HANDLING AND STORAGE

### PRECAUTIONS FOR SAFE HANDLING

PROTECTIVE MEASURES:

Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container. Non equilibrium conditions may increase the fire hazard associated with this product. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards. Carefully review operations that may increase the risks such as tank and container filling, tank cleaning, sampling, gauging,

loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Always keep nozzle in contact with the container throughout the loading process. Do NOT fill any portable container in or on a vehicle.

#### ADVICE ON GENERAL OCCUPATIONAL HYGIENE:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### CONDITIONS FOR SAFE STORAGE INCLUDING ANY INCOMPATIBILITIES:

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### CONTROL PARAMETERS

#### OCCUPATIONAL EXPOSURE LIMITS:

INGREDIENT NAME  
C9-C15 Cycloalkanes

EXPOSURE LIMITS  
ACGIH TLV (United States)  
TWA: 400 ppm 8 hours. Form: Methylcyclohexane

C9-C15 Aromatics

ACGIH TLV (United States)  
TWA: 400 ppm 8 hours. Form: Methylcyclohexane

#### APPROPRIATE ENGINEERING CONTROLS:

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### ENVIRONMENTAL EXPOSURE CONTROLS:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### INDIVIDUAL PROTECTION MEASURES

##### HYGIENE MEASURES:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### EYE/FACE PROTECTION:

Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. chemical splash goggles. If inhalation hazards exist, a full-face respirator may be required instead.

## SKIN PROTECTION

### HAND PROTECTION:

Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

### BODY PROTECTION:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### OTHER SKIN PROTECTION:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### RESPIRATORY PROTECTION:

Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Color	Colorless
Odor	Characteristic hydrocarbon solvent odor
pH	Not available
Melting point	-58°C (-72.4°F)
Boiling point/boiling range	175 to 270°C (347 to 518°F)
Flash point	Closed cup: 80°C (176°F) [Tagliabue (ASTM D-56)]
Evaporation rate	<1 (n-butyl acetate. = 1)
Lower and upper explosive (flammable) limits	Lower: 0.6% / Upper: 5.5%
Vapor pressure	0.03 to 0.06 kPa (0.225 to 0.45 mm Hg) [room temperature]
Vapor density	4.5 [Air = 1]
Relative density	0.819
Density lbs/gal	6.79 lbs/gal
Gravity, °API	Estimated 41 @ 60 F
Solubility	Very slightly soluble in the following materials: cold water.

Solubility in water	1.5 g/l
Auto-ignition temperature	236°C (456.8°F)

## 10. STABILITY AND REACTIVITY

Reactivity	Not expected to be Explosive, Self-Reactive, Self-Heating or an Organic Peroxide under US GHS Definition (s)
Chemical stability	The product is stable
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects  
Acute toxicity

### CONCLUSION/SUMMARY:

C9-C15 Alkanes: In animal studies utilizing mineral spirits containing up to 22% aromatics indicated that the acute central nervous system effects are reversible. Based on existing animal studies, the potential for persistent effects is not clear.

### IRRITATION/CORROSION

PRODUCT NAME	RESULT	SPECIES	SCORE	EXPOSURE	OBSERVATION
C9-C15 Aromatics	Skin-mild irritant	Rabbit	-	24 hours 500 microliters	-

**Skin**  
C9-C15 Alkanes: Primary dermal irritation studies (four hour exposure) in rabbits utilizing mineral spirits containing less than 2% aromatics resulted in slight to moderate skin irritation. In humans, mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented.

**Eyes**  
No additional information

**Respiratory**  
C9-C15 Alkanes: Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations. Also, sensory respiratory tract irritation was evident by reduced breathing rates in the test animals in certain studies.

**Sensitization Skin**  
C9-C15 Alkanes: In animal studies utilizing mineral spirits containing up to 18%, aromatics skin sensitization is not evident.



Respiratory  
No additional information

#### Mutagenicity Conclusion/Summary

C9-C15 Alkanes: In vivo and in vitro studies on mineral spirits containing up to 22 % aromatics indicate that these products are not genotoxic.

#### Carcinogenicity Conclusion/Summary

C9-C15 Alkanes: The National Toxicology Program (NTP) conducted two-year Carcinogenicity studies in rats and mice with Stoddard Solvent IIC (less than 2% aromatics). The studies indicated that there was some evidence of carcinogenic activity in male rats (adrenal medulla neoplasms and renal tubule adenoma) but no evidence of carcinogenic activity in female rats. Further, there was equivocal evidence of carcinogenic activity in female mice (hepatocellular adenoma) but no evidence of carcinogenic activity in male mice. A low carcinogenic potential is suggested by a lack of genotoxic potential identified in in vivo and in vitro genetic toxicity tests (with and without metabolic activation).

#### Reproductive toxicity Conclusion/Summary

C9-C15 Alkanes: There were no treatment-related effects on pregnancy rate, mortality or gross post mortem observations in animal studies utilizing mineral spirits containing less than 2% aromatics.

#### Teratogenicity Conclusion/Summary

C9-C15 Alkanes: There were no treatment-related effects on pregnancy rate, mortality or gross post mortem observations in animal studies utilizing mineral spirits containing less than 2% aromatics.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
C9-C15 Cycloalkanes	Category 3	not applicable	Narcotic effects
C9-C15 Alkanes	Category 3	not applicable	Narcotic effects
C9-C15 Aromatics	Category 3	not applicable	Narcotic effects

Specific target organ toxicity (repeated exposure) NOT AVAILABLE

#### ASPIRATION HAZARD

NAME	RESULT
C9-C15 Cycloalkanes	ASPIRATION HAZARD - CATEGORY 1
C9-C15 Alkanes	ASPIRATION HAZARD - CATEGORY 1
C9-C15 Aromatics	ASPIRATION HAZARD - CATEGORY 1

#### Information on the likely routes of exposure

Routes of entry anticipated: Oral,Dermal,Inhalation.

#### Potential acute health effects

Eye contact	Causes eye irritation.
Inhalation	Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
Skin contact	Causes skin irritation.
Ingestion	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

#### Symptoms related to the physical, chemical and toxicological characteristics

##### EYE CONTACT:

Adverse symptoms may include the following: pain or irritation  
watering  
redness



**INHALATION:**

Adverse symptoms may include the following:

- nausea or vomiting
- headache
- drowsiness/fatigue
- dizziness/vertigo unconsciousness

**SKIN CONTACT:**

Adverse symptoms may include the following: Irritation and redness

**INGESTION:**

Adverse symptoms may include the following: nausea or vomiting

**Potential chronic health effects**

General	No known significant effects or critical hazards
Carcinogenicity	No known significant effects or critical hazards
Mutagenicity	No known significant effects or critical hazards
Teratogenicity	No known significant effects or critical hazards
Developmental effects	No known significant effects or critical hazards
Fertility effects	No known significant effects or critical hazards

**12. ECOLOGICAL INFORMATION**

**TOXICITY**

**PRODUCT/**

**INGREDIENT NAME** SOLVENT 500

**RESULT:**

Acute LC50 2200 µg/l Fresh water	SPECIES: Fish-Lepomis macrochirus	EXPOSURE: 4 days
Acute LC50 2600 µg/l Fresh water	SPECIES: Fish-oncorhynchus mykiss	EXPOSURE: 4 days
Acute LC50 2900 µg/l Fresh Water	SPECIES: Fish-Oncorhynchus mykiss	EXPOSURE; 4 DAYS

**CONSLUSION/SUMMARY:** NOT AVAILABLE

**PERSISTENCE AND DEGRADABILITY:** NOT AVAILABLE

**CONCLUSION/SUMMARY** NOT AVAILABLE

**BIOACCUMULATIVE POTENTIAL**

<b>PRODUCT/INGREDIENT NAME</b>	<b>LogPow</b>	<b>BCF</b>	<b>Potential</b>
C9-C15 Aromatics	2.8 to 6.5	99 to 5780	High

**Mobility in soil**

Soil/water partition coefficient (KOC) NOT AVAILABLE

Other adverse effects No known significant effects or critical hazards.

**13. DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA CLASSIFICATION: D018

## 14. TRANSPORT INFORMATION

CFR

PROPER SHIPPING NAME	PETROLEUM DISTILLATES, N.O.S.
UN NUMBER:	1268
CLASS	3
PACKING GROUP:	II
HAZARD:	COMBUSTIBLE LIQUID

TDG:

PROPER SHIPPING NAME	PETROLEUM DISTILLATES, N.O.S.
UN NUMBER:	1268
CLASS	3
PACKING GROUP:	II
HAZARD:	COMBUSTIBLE LIQUID

### IATA CARGO TRANSPORT

UN UN-No.	UN1268
Description of Goods	PETROLEUM DISTILLATES, N.O.S. (naptha; low boiling Point naphtha)
Class	3
Packaging Groups	II
ICAO-Labels	3
Packing Instruction (cargo aircraft)	364
Packing instruction (cargo aircraft)	Y341

### IATA PASSENGER TRANSPORT

UN UN-No.	UN1268
Description of Goods	PETROLEUM DISTILLATES, N.O.S. (naptha; low boiling point naphtha)
Class	3
Packaging Groups	II
ICAO-Labels	3
Packing Instruction (cargo aircraft)	364
Packing instruction (cargo aircraft)	Y341

IMDG-CODE

UN-No. UN 1268  
 Description of Goods PETROLEUM DISTILLATES, N.O.S. (naptha; low boiling point naphtha)

Class 3  
 Packaging group II  
 IMDG-Labels 3  
 EmS Number F-E-S-E  
 Marine Pollutant NO

## 15. REGULATORY INFORMATION

### U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: Naphthalene; Ethylbenzene; Toluene; Benzene

Clean Water Act (CWA) 311: Naphthalene; Ethylbenzene; Toluene; Benzene

This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA).

Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

### SARA 302/304

Composition/information on ingredients

SARA 304RQ NOT APPLICABLE

### SARA 311/312

Classification FIRE HAZARD, IMMEDIATE (ACUTE) HEALTH HAZARD

### COMPOSITION/INFORMATION ON INGREDIENTS

NAME	FIRE HAZARD	SUDDEN RELEASE OF PRESSURE	REACTIVE	IMMEDIATE (acute) Health hazard	DELAYED (Chronic) Health Hazard
C9-C15 Cycloalkanes	yes	no	no	yes	no
C9-C15 Alkanes	yes	no	no	yes	no
C9-C15 Aromatics	yes	no	no	yes	no

State regulations None of the components are listed.

Massachusetts None of the components are listed.

New York None of the components are listed.

New Jersey None of the components are listed.

Pennsylvania None of the components are listed.

California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum Acceptable dosage level
TOLUENE	<0.001	NO	YES	NO	7000 µg/day (ingestion)
BENZENE	<0.001	YES	YES	6.4 µg/day (ingestion) 13 µg/day (inhalation)	24 µg/day (ingestion)
Naphthalene	<0.0001	yes	no	yes	no
Ethybenzene	<0.0001	yes	no	41 µg/day (ingestion)	no

International regulations

International lists

Australia inventory(AICS):All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined.

Korea inventory: All components are listed or exempted.

Malaysia Inventory (EHS Register): All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Canada inventory All components are listed or exempted.

EU Inventory : All components are listed or exempted.

WHMIS(Canada) ClassB-3:Combustibleliquidwithaflashpointbetween37.8°C(100°F)and93.3°C (200°F)

## 16. OTHER INFORMATION

### KEY TO ABBREVIATIONS:

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.

("Marpol" = marine pollution)

UN = United Nations

### NOTICE TO READER

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT .

Date Created: 3/20/2015

Date Updated: 6/2/2015