

Product Description

Isopropyl Acetate is a urethane grade, fast evaporating, mild odor solvent that is miscible with most common organic solvents and has properties intermediate between ethyl and butyl acetates.

| Property Acidity as Acetic Acid Assay Autoignition Temperature Blush Resistance @80°F(26.7°C) Boiling Point @760 mm Hg | Units | Specifications | Typical 0.005wt%max 99.6 wt% min 479°C(894°F) 62%RH 85-90°C(185-196°F) | Test Method |
|---|-------|----------------|--|-------------|
| Color, Pt-Co | | | 5max | |
| Critical Pressure | | | 35.3 ATM | |
| Critical Temperature | | | 264.8°C | |
| Critical Volume | | | 336 ml/g mol | |
| Dilution Ratio | | | 2 | |
| | | | 3 | |
| VMP Naphtha | | | 1.2 | |
| Expansion Coefficient, per°C @ 20°C | | | 0.00131 | |
| Flash Point Closed cup | | | 2°C (35°F) | |
| Freezing Point | | | -73°C(-99°F) | |
| Heat of Combustion | | | -635.3kcal/g mol | |
| Heat of Vaporization | | | 7703 cal/g mol 47.66 cal/(g*mol)(°C) | |
| Liquid Heat Capacity @ 25°C | | | | |
| Liquid Viscosity @ 20°C | | | 0.6 cP(mPa s) 1.38 | |
| Refractive Index @ 20°C | | | 0.873 | |
| Specific Gravity @ 20/20°C | | | | |
| Vapor Density (air=1) | | | 3.5 | |
| Vapor Pressure: @ 20°C | | | 47.5 mm Hg | |
| @55°C | | | 30.7 KPa 0.87 kg/L (7.25lb/gl) | |
| Wt/Vol @ 20°C | | | 5.07 Ng/E (1.2010/91) | |



Item Number

Date Created 6/23/2015

Date Updated 6/23/2015



CAROLINA INTERNATIONAL SALES CO., INC. 266 Rue Cezzan Lavonia, GA 30553 770-904-7042 www.ciscochem.com

Limitations of Warranty & Liability

Seller warrants its product will meet the specifications listed herein and it has good title to the product, free and clear of all liens and security interests; SELLER MAKES NO OTHER WARRANTY, WHETHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Buyer or user accepts liability for determining if the product is suitable for Buyer's or user's intended use. Any recommendation as to use made by Seller is done so at Buyer's or user's risk.

Buyer shall assume all risk and liability for and shall defend, indemnify, and hold Seller harmless from and against all claims, liabilities, costs, and expenses arising from or connected with the possession, transportation, handling, unloading, storage, processing or use of the product alone or in combination with other substances. Buyer's exclusive remedy and Seller's exclusive liability for damages under contract, tort, strict liability, negligence, or otherwise, shall be limited at Seller's option to the refund of the purchase price or the replacement of the product. In no event shall Seller be liable for incidental, indirect, special, or consequential damages.

Buyer acknowledges receipt of a Material Safety Data Sheet for the product and that the product may require special handling, storage, transportation, treatment or use to comply with applicable safety and environmental standards and will take all necessary action to comply therewith. Buyer further agrees to properly label the product if it is repackaged or resold and pass on all safety information and hazard warnings to its employees, purchasers, and users and their employees.